

Product Information Bulletin

March
2010

FABGRIP 1906 HI -TAC MULTI PURPOSE VOC COMPLIANT RESILIENT FLOORING ADHESIVE

DESCRIPTION

Fabgrip 1906 is a semi-pressure sensitive, solvent free, VOC compliant multipurpose resilient flooring adhesive. 1906 was especially formulated to give high tack and trouble free installation to most types of sheet vinyl, vinyl plank and tile and rubber floor-coverings in dry areas to most common interior sub-floors.

CHARACTERISTICS

- * Water based
- * Solvent Free
- * Semi-pressure sensitive
- * Spreads easily
- * Aggressive tack
- * Economical
- * Can be heat reactivated
- * VOC compliant
- * Excellent ageing resistance
- * Coverage; 5m²/ltr
- * Available in; 15ltr pails

SURFACE PREPARATION:

All sub-floor surfaces shall be dry, smooth, sound and clean, free of wax, grease and all other contaminants that inhibit adequate adhesion to the sub-floor. The sub-floor must also be free from hydrostatic pressure or capillary action. The adhesive should not be used in excessive cold or hot conditions i.e. below 8°C or above 28°C.

It is recommended that highly porous timber or concrete sub-floor surfaces be primed with Primer 88 and allowed to cure before applying adhesive.

Uneven or damaged floors should be repaired with a cementitious levelling compound. All subfloors should be tested for moisture content prior to surface priming or application of adhesive. All sub-floors should in accordance with current Australian standard installation practices.

APPLICATION:

Apply 1906 with the specified "V" notched trowel. Apply an even coat to a manageable area. Allow the adhesive to tack up before installing the floor-covering. In humid or cold conditions ensure that the adhesive has sufficient tack before laying the floor-covering. Roll the floor-covering to manufacturer's instructions. Do not allow heavy traffic within 24 hours after installing the floor-covering.

CLEAN UP: Clean tools and equipment immediately with warm soapy water. To remove dried adhesive use Holdfast Super Cleaning Solvent.

CAUTION

Do not allow adhesive to freeze, unaffected by freezing when dry. This adhesive has a shelf life of 12 months from date of manufacture providing the adhesive is unopened and stored undercover at 20°C.

VENTILATION

Always make sure that there is adequate ventilation when using this adhesive.

CONDITIONS OF SALE: contain a limited warranty against manufacturing defects.

NOTICE TO THE PURCHASER

All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Users assume all risk and liability resulting from the use of this product and must confirm the suitability thereof by their own tests.

CONTACT POINT: Technical Manager
TELEPHONE: (02) 9316 4655