

Product Information Bulletin

March
2010

FABGRIP HI-TAC 2003 COMMERCIAL VINYL ADHESIVE

DESCRIPTION:

Fabgrip 2003 is a premium, water based, high performance semi P.S. vinyl adhesive. 2003 was designed for bonding most types of homogeneous & heterogeneous sheet vinyl, to most common interior sub-floors.

CHARACTERISTICS

- * Water Based
- * Non Flammable
- * Aggressive tack
- * Excellent bonding
- * Economical
- * Can be heat reactivated
- * Spreads easily
- * Excellent ageing resistance
- * Coverage; 5m²/ltr
- * Available in: 15ltr, 4ltr & 1ltr pails

SURFACE PREPARATION:

All subfloor surfaces shall be dry, smooth, sound and clean, free of wax, grease, oil, old adhesive, paint, curing compounds, laitance, bond breakers and all other contaminants that inhibit adequate adhesion to the sub-floor. The sub-floor must also be free from hydrostatic pressure or capillary action. The adhesive should not be used in excessive cold or hot conditions i.e. below 8°C or above 28°C.

It is recommended that highly porous timber or concrete sub-floor surfaces be primed with Primer 88 or 44 and allowed to cure before applying the adhesive.

Uneven or damaged floors should be repaired with a cementitious levelling compound. All subfloors should be tested for moisture content prior to surface priming or application of this adhesive. The moisture content of the sub-floor should not exceed 5.5% and or the relative humidity should not exceed 70%. Do not use this adhesive if the moisture content /relative humidity levels are above the acceptable standards. All subfloors should in accordance with current Australian standard installation practices.

APPLICATION:

With a 1.6 x 1.6 x 1.6mm "V" notched trowel apply an even coat to the surface. Spread only sufficient adhesive to an area, and do not allow the adhesive to form a skin before laying the sheet vinyl. Install the floor-covering onto the tacked up adhesive. Complete the installation according to the manufacturer's instructions, ensuring the installation is rolled in both directions with the recommended roller, prior to the adhesive setting. Do not allow heavy traffic for 24 hours. The product can be re-activated for up to 5 days after the installation.

CLEAN UP:

Clean tools and equipment immediately with warm soapy water. To remove dried adhesive use Holdfast Super Cleaning Solvent with care.

CAUTION

Do not allow adhesive to freeze, unaffected by freezing when dry. This adhesive has a shelf life of 12 months from date of manufacture providing the adhesive is unopened and stored undercover at 20°C.

VENTILATION

Always make sure that there is adequate ventilation when using this adhesive.

CONDITIONS OF SALE: contain a limited warranty against manufacturing defects.

NOTICE TO THE PURCHASER

All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Users assume all risk and liability resulting from the use of this product and must confirm the suitability thereof by their own tests.

CONTACT POINT: Technical Manager

TELEPHONE: (02) 9316 4655