

Product Information Bulletin

March
2010

FABGRIP 267 DIRECT STICK CARPET ADHESIVE

DESCRIPTION

Fabgrip 267 is a water based carpet adhesive. 267 was designed to bond most tufted and needle punched carpets to most common interior sub-floors. 267 was developed as a quick grab fast setting carpet adhesive.

CHARACTERISTICS

- * Water based
- * High initial tack
- * Spreads easily
- * Economical
- * Tack up; 15-20 minutes
- * Coverage; 3-4m²/ltr
- * Available in; 15ltr,4ltr & 1ltr pails

SURFACE PREPARATION

All subfloor surfaces shall be dry, smooth, sound and clean, free of wax, grease, oil, old adhesive, paint, curing compounds, laitance, bond breakers and all other contaminants that inhibit adequate adhesion to the sub-floor. The sub-floor must also be free from hydrostatic pressure or capillary action. The adhesive should not be used in excessive cold or hot conditions i.e. below 8°C or above 28°C.

It is recommended that highly porous timber or concrete sub-floor surfaces be primed with Primer 88 or 44 and allowed to cure before applying the adhesive.

Uneven or damaged floors should be repaired with a cementitious levelling compound. All subfloors should be tested for moisture content prior to surface priming or application of this adhesive. The moisture content of the sub-floor should not exceed 5.5% and or the relative humidity should not exceed 70%. Do not use this adhesive if the moisture content /relative humidity levels are above the acceptable standards. All subfloors should in accordance with current Australian standard installation practices.

APPLICATION

TROWEL SIZES:

Smooth backed carpets	2.4 x 2.4 x 2.4 mm "V" notched trowel
Textured back carpets and Needle Punched	3.2 x 1.6 x 3.2 mm "V" notched trowel

Stir adhesive before use. Spread adhesive with the recommended "V" notched trowel. Allow the adhesive to tack up before the floor covering is lowered onto the adhesive. Roll the floorcovering as per manufacturer's instructions. All seams must be sealed using Holdfast Seemweld. Do not allow traffic for 24 hours.

NOTE

Shrinkage may occur with certain types of jute backed tufted or woven carpets, please ensure to adjust installation methods prior to the commencement of the installation if the floor-covering could be prone to shrinkage.

CLEAN UP

Clean tools and equipment immediately with warm soapy water. To remove dried adhesive use Holdfast Super Cleaning Solvent.

CAUTION

Do not allow adhesive to freeze, unaffected by freezing when dry. This adhesive has a shelf life of 12 months from date of manufacture kept in unopened containers undercover at 20°C.

VENTILATION

Always make sure that there is adequate ventilation when using this adhesive.

CONDITIONS OF SALE: contain a limited warranty against manufacturing defects.

NOTICE TO THE PURCHASER

All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Users assume all risk and liability resulting from the use of this product and must confirm the suitability thereof by their own tests.

CONTACT POINT: Technical Manager
TELEPHONE: (02) 9316 4655