

Product Information Bulletin

March
2010

FABGRIP 4002 MULTI PURPOSE LOW ODOUR SOLVENT FREE RESILIENT FLOORING ADHESIVE

DESCRIPTION:

4002 is a low odour, solvent free, water based acrylic co-polymer adhesive. 4002 was specifically formulated to bond most types of sheet vinyl, vinyl plank and tile to most common interior sub-floors.

CHARACTERISTICS

- * Low odour
- * Solvent free
- * Economical
- * Excellent ageing resistance
- * Aggressive tack
- * Coverage; 5m²/ltr
- * Available in; 15ltr & 4ltr pails

SURFACE PREPARATION

All sub-floor surfaces shall be dry, smooth, sound and clean, free of wax, grease and all other contaminants that inhibit adequate adhesion to the sub-floor. The sub-floor must also be free from hydrostatic pressure or capillary action. The adhesive should not be used in excessive cold or hot conditions i.e. below 8°C or above 28°C.

It is recommended that highly porous timber or concrete sub-floor surfaces be primed with Primer 88 and allowed to cure before applying adhesive.

Uneven or damaged floors should be repaired with a cementitious levelling compound. All subfloors should be tested for moisture content prior to surface priming or application of adhesive. All sub-floors should in accordance with current Australian standard installation practices.

APPLICATION

Apply 4002 Solvent Free Adhesive evenly to floor using the recommended "V" notched trowel. Do not spread more adhesive than can be laid before the adhesive skins over for optimum transfer. Allow adhesive to tack up for 10-20 minutes depending on temperature, humidity and substrate. Install the floor-covering into the tacked up adhesive to ensure good adhesive transfer, roll the floor-covering with the recommended roller and rub down to remove irregularities. Complete installation according to floor-covering manufacturer's instructions. Do not allow heavy traffic for 24 hours.

CLEAN UP

Clean tools and equipment with warm soapy water. To remove dried adhesive use Holdfast Super Cleaning Solvent with care.

STORAGE AND USAGE

Use in well ventilated areas. Keep container closed, store away from sources of heat. Do not allow adhesive to freeze, unaffected by freezing when dry. This adhesive has a shelf life of 12 months from date of manufacture providing the adhesive is unopened and stored undercover at 20°C.

VENTILATION

Always make sure that there is adequate ventilation when using this adhesive.

CONDITIONS OF SALE: contain a limited warranty against manufacturing defects.

NOTICE TO THE PURCHASER

All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Users assume all risk and liability resulting from the use of this product and must confirm the suitability thereof by their own tests.

CONTACT POINT: Technical Manager
TELEPHONE: (02) 9316 4655