

Product Information Bulletin

March
2010

FABGRIP 480 P.S ADHESIVE

DESCRIPTION:

Fabgrip 480 is a solvent free, low odour, pressure sensitive adhesive. 480 was specifically formulated for installing reinforced vinyl composition tiles. 480 was also designed for bonding, most double bond underlay's to most common interior subfloors.

CHARACTERISTICS

- * Solvent free
- * Low odour
- * Permanently pressures sensitive
- * Economical
- * Spreads easily
- * Excellent ageing resistance
- * Available in: 15ltr & 4ltr pails
- * Coverage: 6-8m²/ltr

SURFACE PREPARATION

All subfloor surfaces shall be dry, smooth, sound and clean, free of wax, grease, oil, old adhesive, paint, curing compounds, laitance, bond breakers and all other contaminants that inhibit adequate adhesion to the sub-floor. The sub-floor must also be free from hydrostatic pressure or capillary action. The adhesive should not be used in excessive cold or hot conditions i.e. below 8°C or above 28°C.

It is recommended that highly porous timer or concrete sub-floor surfaces be primed with Primer 88 or 44 and allowed to cure before applying the adhesive.

Uneven or damaged floors should be repaired with a cementitious levelling compound. All subfloors should be tested for moisture content prior to surface priming or application of this adhesive. The moisture content of the sub-floor should not exceed 5.5% and or the relative humidity should not exceed 70%. Do not use this adhesive if the moisture content /relative humidity levels are above the acceptable standards. All subfloors should in accordance with current Australian standard installation practices.

APPLICATION

Vinyl Composition Tiles

Apply the adhesive to sub-floor with a V1 (1.6 x 1.6 x 1.6mm) "V" notched trowel. Spread as much adhesive as desired, allow the adhesive to dry. Drying time is approx. 25-45 minutes depending on temperature, humidity and the substrate. The adhesive will change from milky colour when wet to clear tacky product when dry. This tack remains indefinitely, providing the adhesive is free from dust. Install vinyl tiles onto the dry adhesive. The pressure sensitive properties of 480 allow for uninterrupted application of adhesive and tiles. Subsequently large areas may be tiled in a given time. Roll the vinyl tiles as per manufacturer's instructions.

DOUBLE BOND UNERLAY

Apply the adhesive to the sub-floor with a V1 (1.6 x 1.6 x 1.6mm) “V” notched trowel. Allow the adhesive to tack up for 10-15 minutes, install the underlay into the tacked up adhesive. Roll the underlay per manufacturers instructions.

CLEAN UP

Clean tools and equipment with warm soapy water. To remove dried adhesive use Holdfast Super Cleaning Solvent with care.

STORAGE AND USAGE

Use in well ventilated areas. Keep container closed, store away from sources of heat. Do not allow adhesive to freeze, unaffected by freezing when dry. This adhesive has a shelf life of 12 months from date of manufacture providing the adhesive is unopened and stored undercover at 20°C.

VENTILATION

Always make sure that there is adequate ventilation when using this adhesive.

CONDITIONS OF SALE: contain a limited warranty against manufacturing defects.

NOTICE TO THE PURCHASER

All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Users assume all risk and liability resulting from the use of this product and must confirm the suitability thereof by their own tests.

CONTACT POINT: Technical Manager
TELEPHONE: (02) 9316 4655