

Product Information Bulletin

March
2010

HOLDFAST 60% LATEX

DESCRIPTION

Holdfast 60% latex is used for adhering underfelt for most surfaces. It may also be used to prevent fraying of the edges of woven carpets and for patching and repairing fabrics such as canvas.

CHARACTERISTICS AND ADVANTAGES

- * Water based
- * Economical
- * Ammonia odour
- * Available in; 20ltr, 20ltr, 4ltr & 1ltr sizes
- * Coverage; up to 15m²/ltr

SURFACE PREPARATION

All subfloor surfaces shall be dry, smooth, sound and clean, free of wax, grease, oil, old adhesive, paint, curing compounds, laitance, bond breakers and all other contaminants that inhibit adequate adhesion to the sub-floor. The sub-floor must also be free from hydrostatic pressure or capillary action. The adhesive should not be used in excessive cold or hot conditions i.e. below 8°C or above 28°C.

Uneven or damaged floors should be repaired with a cementitious levelling compound. All subfloors should be tested for moisture content prior to surface priming or application of this adhesive. The moisture content of the sub-floor should not exceed 5.5% and or the relative humidity should not exceed 70%. Do not use this adhesive if the moisture content /relative humidity levels are above the acceptable standards. All subfloors should in accordance with current Australian standard installation practices.

APPLICATION

Shake before using. Apply a liberal layer on subfloor surface. Spread with a sponge or roller and press underfelt while still wet. Adhesion occurs immediately, but full strength is not attained for several hours.

PRECAUTIONS

In common with all rubber based products contamination with extremely low concentrations of copper, manganese, brass and zinc will cause rapid ageing of the rubber.

CAUTION

Do not allow adhesive to freeze, unaffected by freezing when dry. This product has a shelf life of 12 months in unopened containers kept under cover at 20°C.

CLEAN UP

Clean tools and equipment immediately with cold water.

VENTILATION

Always make sure that there is adequate ventilation when using this adhesive.

CONDITIONS OF SALE: contain a limited warranty against manufacturing defects.

NOTICE TO THE PURCHASER

All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Users assume all risk and liability resulting from the use of this product and must confirm the suitability thereof by their own tests.

CONTACT POINT: Technical Manager
TELEPHONE: (02) 9316 4655