

# TIMBER & CORK flooring adhesives



## features & benefits

Adhesive	
<b>170</b>	170 is a water based flexible P.V.A adhesive specifically formulated for the installation of most types of Mosaic and 19mm block parquet flooring. 170 is available in both yellow and brown colours for light and dark timbers, 170 has a solid content of approx. 70%. 170 is an economical highly flexible adhesive that is easy to spread and also develops an extremely high final bond strength.
<b>180</b>	180 is a water based flexible Co-polymer adhesive specifically formulated for the installation of most types of Mosaic parquet, 19mm and 14mm block parquet. 180 can also be used for most types of timber overlay installations. 180 is available in both yellow and brown colours for light and dark timbers, 180 has a solid content of approx. 80%. 180 is a economical high solid adhesive that displays flexibility and faster curing time for sanding and finishing.
<b>501</b>	501 is a two pac polyurethane adhesive specifically designed for block & mosaic parquet flooring. 501 contains no moisture & is available in both Yellow & Brown for light and dark timbers. 501 has a superior drying time than other similar adhesives. 501 has a superior curing time which allows for parquet flooring to be sanded 72 hours after the installation is complete.
<b>DN175</b>	DN175 is a single part cross-linked water resistant D3 rated PVA adhesive. DN175 was specifically designed for the installation of glue together tongue and groove floating timber and laminate floors. DN175 is a non-staining clear drying flexible adhesive and is packaged in a 500ml bottle with an ergonomic designed step cap top for varied grooved heights.
<b>502/P</b>	502/P is a natural latex contact adhesive. 502/P was specifically formulated for the installation of adhesive backed cork floor tiles. 502/P is a quick drying easy to apply adhesive that displays high coverage rates.
<b>285</b>	285 is a latex based adhesive that was developed for the installation of most Cork floor tiles. 285 displays a high initial tack and also allows the installer excellent working time.
<b>7800</b>	Uroset 7800 is a one part solvent free moisture cured polyurethane adhesive. 7800 was specifically developed for bonding most types of timber flooring systems to internal sub-floors. 7800 is a flexible adhesive that displays excellent bond strength, 7800 is easy to apply to the substrate and is available in both yellow and brown colours.
<b>UMB</b>	Uroseal Moisture Barrier is a 2 part solvent free epoxy sealer. UMB was designed as a moisture barrier/sealer for most concrete and timber sub-floors. UMB is a multi coat system that is easy to apply and acts as a moisture suppressant for most sub-floors that contain moisture readings of above 5%.



## FABGRIP **TIMBER** & **CORK** flooring adhesives *selection Guide*

Fabgrip	Mosaic parquetry	19mm block	14mm block	Floating floors	Overlay flooring	Cork acoustic underlay	Cork flooring	Rubber acoustic underlay
<b>170</b>								
<b>180</b>								
<b>501</b>								
<b>DN175</b>								
<b>502/P</b>								
<b>285</b>								
<b>7800</b>								

Fabgrip	Base	Coverage	Open time	Trowel notching	Primer	Sand & coat
<b>170</b>	PVA	0.8–1.5m <sup>2</sup> /ltr	15–30 mins	U3 Mosaic V5 Block	Refer to PIB	10–14 days
<b>180</b>	Co-Polymer	0.7–1m <sup>2</sup> /ltr	15–30 mins	U3 Mosaic V5 Block	Refer to PIB	7–10 days
<b>501</b>	2 part Polyurethane	0.7–1m <sup>2</sup> /ltr	POT LIFE 60–90 mins	U3 Mosaic V5 Block	Refer to PIB	72 hours
<b>DN175</b>	Cross-linked PVA	8–10m <sup>2</sup> /500ml	DRY TIME 24 hours	Step cap nozzle	n/a	n/a
<b>502/P</b>	Natural latex	8–10m <sup>2</sup> /ltr	DRY TIME 1–2 hours	Flat trowel or roller	323	24 hours
<b>285</b>	Natural latex	4–6m <sup>2</sup> /ltr	10–20 mins	V1	Refer to PIB	48 hours
<b>7800</b>	Base Polyurethane	0.8–1.5m <sup>2</sup> /ltr	30 mins	Refer to PIB	HMB	n/a

Distributed by...

# Fabgrip

**Holdfast**® Fabgrip adhesives  
for the 21st Century

HOLDFAST ADHESIVES (AUST) PTY LTD  
90-92 BAY STREET BOTANY NSW 2019  
PH (02) 9316 4655 FAX (02) 9316 4223  
e-mail info@holdfastadhesives.com.au



# FABGRIP **TIMBER** & **CORK** flooring adhesives *selection Guide*

Fabgrip	Mosaic parquetry	19mm block	14mm block	Floating floors	Overlay flooring	Cork acoustic underlay	Cork flooring	Rubber acoustic underlay
<b>170</b>								
<b>180</b>								
<b>501</b>								
<b>DN175</b>								
<b>502/P</b>								
<b>285</b>								
<b>7800</b>								

Fabgrip	Base	Coverage	Open time	Trowel notching	Primer	Sand & coat
<b>170</b>	PVA	0.8–1.5m <sup>2</sup> /ltr	15–30 mins	U3 Mosaic V5 Block	Refer to PIB	10–14 days
<b>180</b>	Co-Polymer	0.7–1m <sup>2</sup> /ltr	15–30 mins	U3 Mosaic V5 Block	Refer to PIB	7–10 days
<b>501</b>	2 part Polyurethane	0.7–1m <sup>2</sup> /ltr	POT LIFE 60–90 mins	U3 Mosaic V5 Block	Refer to PIB	72 hours
<b>DN175</b>	Cross-linked PVA	8–10m <sup>2</sup> /500ml	DRY TIME 24 hours	Step cap nozzle	n/a	n/a
<b>502/P</b>	Natural latex	8–10m <sup>2</sup> /ltr	DRY TIME 1–2 hours	Flat trowel or roller	323	24 hours
<b>285</b>	Natural latex	4–6m <sup>2</sup> /ltr	10–20 mins	V1	Refer to PIB	48 hours
<b>7800</b>	Base Polyurethane	0.8–1.5m <sup>2</sup> /ltr	30 mins	Refer to PIB	HMB	n/a

Distributed by...

# Fabgrip

**Holdfast**® Fabgrip adhesives  
for the 21st Century

HOLDFAST ADHESIVES (AUST) PTY LTD  
90-92 BAY STREET BOTANY NSW 2019  
PH (02) 9316 4655 FAX (02) 9316 4223  
e-mail info@holdfastadhesives.com.au