

Product Information Bulletin

March
2010

FABGRIP CF27 CONDUCTIVE VINYL SHEETING ADHESIVE

DESCRIPTION:

Fabgrip CF27 is a water based, pigment black adhesive specifically formulated for bonding various conductive and antistatic sheet vinyl floor-coverings, to comply with specifications required for volumetric resistance to most common interior sub-floors.

CHARACTERISTICS

- * Water based
- * Non flammable
- * Economical
- * Easy to spread
- * One way wet stick
- * Available in: 15ltr pails
- * Coverage: 4-5m²/ltr

SURFACE PREPARATIONS:

All subfloor surfaces shall be dry, smooth, sound and clean, free of wax, grease, oil, old adhesive, paint, curing compounds, laitance, bond breakers and all other contaminants that inhibit adequate adhesion to the sub-floor. The sub-floor must also be free from hydrostatic pressure or capillary action. The adhesive should not be used in excessive cold or hot conditions i.e. below 8°C or above 28°C.

It is recommended that highly porous timber or concrete sub-floor surfaces be primed with a conductive primer and allowed to cure before applying the adhesive.

Uneven or damaged floors should be repaired with a cementitious levelling compound. All subfloors should be tested for moisture content prior to surface priming or application of this adhesive. The moisture content of the sub-floor should not exceed 5.5% and or the relative humidity should not exceed 70%. Do not use this adhesive if the moisture content /relative humidity levels are above the acceptable standards. All subfloors should in accordance with current Australian standard installation practices.

APPLICATION:

Stir adhesive before use. Apply the adhesive with a V1 (1.6 x 1.6 x 1.6mm) "V" notched trowel to the sub-floor. Allow the adhesive to tack up for approx. 15-20 minutes then install the floor-covering into the adhesive. Roll and complete the floor-covering as per manufactures instructions.

CLEAN UP: Remove excess adhesive whilst still wet with a damp cloth, dry adhesive may be removed using Holdfast Super Cleaning Solvent with care.

STORAGE AND USAGE

Use in well ventilated areas. Keep container closed, store away from sources of heat. Do not allow adhesive to freeze, unaffected by freezing when dry. This adhesive has a shelf life of 6 months from date of manufacture providing the adhesive is unopened and stored undercover at 20°C.

VENTILATION

Always make sure that there is adequate ventilation when using this adhesive.

CONDITIONS OF SALE: contain a limited warranty against manufacturing defects.

NOTICE TO THE PURCHASER

All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Users assume all risk and liability resulting from the use of this product and must confirm the suitability thereof by their own tests.

CONTACT POINT: Technical Manager
TELEPHONE: (02) 9316 4655