

Product Information Bulletin

March
2010

## **PRIMER 88**

### **DESCRIPTION:**

PRIMER 88 is a water based acrylic primer specifically formulated to be used where subfloors are porous. Primer 88 should be broken down 1 part primer to 1 - 2 parts water.

### **CHARACTERISTICS & ADVANTAGES**

- \* Water based
- \* VOC compliant
- \* Non flammable
- \* Fast setting
- \* Easy to apply
- \* Economical
- \* Good water resistance
- \* Also acts as a sealer to prevent premature drying of adhesive
- \* Available in; 15ltr pails
- \* Coverage; 12-15m<sup>2</sup>/ltr

### **SURFACE PREPARATIONS:**

All subfloor surfaces shall be dry, smooth, sound and clean, free of wax, grease, curing compounds and hydrostatic pressure or capillary action. Primer should not be used in excessive cold or hot conditions i.e. below 8°C or above 28°C. All concrete sub-floors should be tested for moisture content prior to undertaking surface priming and should be in accordance with current Australian Standards.

### **APPLICATION:**

The primer should be applied evenly over the entire subfloor by using a sponge, brush or roller. Allow primer to completely cure before applying adhesive.

### **STORAGE AND USAGE**

Use in well ventilated areas. Keep container closed, store away from sources of heat. Do not allow adhesive to freeze, unaffected by freezing when dry. This adhesive has a shelf life of 12 months from date of manufacture providing the adhesive is unopened and stored undercover at 20°C.

### **VENTILATION**

Always make sure that there is adequate ventilation when using this adhesive.

**CONDITIONS OF SALE:** contain a limited warranty against manufacturing defects.

### **NOTICE TO THE PURCHASER**

All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Users assume all risk and liability resulting from the use of this product and must confirm the suitability thereof by their own tests.

**CONTACT POINT:** Technical Manager

**TELEPHONE:** (02) 9316 4655