

Product Information Bulletin

MAY
2008

PRO PRIMER

DESCRIPTION:

Pro Primer is a water based acrylic primer with Anti – Microbial and Anti – Urine odour properties. Pro Primer was specifically formulated to seal most forms of common interior concrete sub-floors. Pro primer was developed to seal sub-floors for Aged care facilities, Hospitals and Childcare facilities.

CHARACTERISTICS & ADVANTAGES

- * Water based
- * Non flammable
- * Fast setting
- * Coverage 12-15m²/ltr
- * Easy to apply
- * Excellent Anti- Microbial performance
- * Neutralises/ stops urine odour
- * Also acts as a sealer to prevent premature drying of adhesive

SURFACE PREPARATIONS:

All subfloor surfaces shall be dry, smooth, sound and clean, free of wax, grease, and hydrostatic pressure or capillary action. Primer should not be used in excessive cold or hot conditions i.e. below 8°C or above 35°C. All concrete substrate floors should be tested for moisture content prior to undertaking surface priming and should be in accordance with current Australian Standards.

APPLICATION:

The primer should be applied evenly over the entire sub-floor by using a sponge, brush or roller. Allow primer to completely dry before applying a second coat of primer. Once the second coat has cured apply the adhesive to the dry film of primer.

STORAGE AND USAGE

Use in well ventilated areas. Keep container closed, store away from sources of heat. Do not allow adhesive to freeze, unaffected by freezing when dry. This adhesive has a shelf life of 12 months from date of manufacture providing the adhesive is unopened and stored undercover at 20°C.

VENTILATION

Always make sure that there is adequate ventilation when using this adhesive.

CONDITIONS OF SALE: contain a limited warranty against manufacturing defects.

NOTICE TO THE PURCHASER

All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Users assume all risk and liability resulting from the use of this product and must confirm the suitability thereof by their own tests.

CONTACT POINT: Technical Manager

TELEPHONE: (02) 9316 4655