

Product Information Bulletin

March
2010

FABGRIP SG226 INDOOR/OUTDOOR SYNTHETIC TURF ADHESIVE**DESCRIPTION:**

SG226 is a solvent based adhesive specifically formulated for bonding synthetic turf and needle punch carpets to most common interior and exterior sub-floors. 226 may also be used for sporting field installations with approved joining tapes. SG226 is not recommended for urethane or EVA backed carpets.

CHARACTERISTICS

- * Solvent based
- * Highly flammable
- * Aggressive tack
- * High bond strength
- * Excellent water resistance
- * Excellent heat resistance
- * Economical
- * Ease of application
- * Available in: 20ltr, 4ltr & 1ltr containers
- * Coverage; 2-3m²/ltr

SURFACE PREPARATION

All subfloor surfaces shall be dry, smooth, sound and clean, free of wax, grease, oil, old adhesive, paint, curing compounds, laitance, bond breakers and all other contaminants that inhibit adequate adhesion to the sub-floor. The sub-floor must also be free from hydrostatic pressure or capillary action. The adhesive should not be used in excessive cold or hot conditions i.e. below 8°C or above 28°C.

Uneven or damaged floors should be repaired with a cementitious levelling compound. All subfloors should be tested for moisture content prior to surface priming or application of this adhesive. The moisture content of the sub-floor should not exceed 5.5% and or the relative humidity should not exceed 70%. Do not use this adhesive if the moisture content /relative humidity levels are above the acceptable standards. All subfloors should in accordance with current Australian standard installation practices.

APPLICATION

Stir the adhesive thoroughly before use. For synthetic grass applications, apply the adhesive with a V5 trowel and for needle punched carpet installations apply the adhesive with a V3 trowel. Install the floor-covering into adhesive whilst the adhesive is still wet. As work proceeds, remove any excess adhesive off pile surface or surrounds. As the adhesive is solvent based, when laying outside make sure that the weather conditions are conducive to laying, as the adhesive takes 4 hours to cure, before being water resistant, and 48 hours before being water proof. It is advisable to use plastic or polythene sheeting to cover work areas if weather becomes unsettled. Roll the floor-covering per the manufacturer's instructions.

HANDLING PRECAUTIONS

This product is flammable. Use only in well ventilated areas. Keep away from heat, sparks and naked flames. Avoid contact with skin and eyes. Avoid breathing vapours, if swallowed do not induce vomiting, give plenty of water or milk and contact a doctor.

CAUTION

Do not allow adhesive to freeze, unaffected by freezing when dry. This adhesive has a shelf life of 12 months from date of manufacture, providing the pail is unopened and under cover at 20°C.

CLEAN UP

To clean up tools, equipment and wet or dry adhesive use Holdfast Super Cleaning Solvent.

VENTILATION

Always make sure that there is adequate ventilation when using this adhesive.

CONDITIONS OF SALE: contain a limited warranty against manufacturing defects.

NOTICE TO THE PURCHASER

All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Users assume all risk and liability resulting from the use of this product and must confirm the suitability thereof by their own tests.

CONTACT POINT: Technical Manager
TELEPHONE: (02) 9316 4655