

Product Information Bulletin

March
2010

## **RIPPER GRIPPER GLUE RAPID SET MOISTURE CURED PU ADHESIVE**

### **DESCRIPTION**

Ripper Gripper Glue is a single part moisture cured rapid setting polyurethane adhesive. Ripper Gripper has been designed for bonding carpet gripper to highly dense concrete sub-floors, ceramic tiles and other hard to nail into sub-floors. The unique nature of Ripper Gripper allows for expansion of adhesive post adhesive placement, as a result, usage of this product is significantly lower than that of other similar adhesives. The rapid setting nature of Ripper Gripper allows for stretching of carpet approx 1 hour after gripper placement.

### **CHARACTERISTICS**

- \* Polyurethane
- \* Rapid setting
- \* Low odour
- \* Spreads easily from a squeeze bottle
- \* Economical
- \* Stretch in time; 60 minutes post application
- \* Available in; 500ml squeeze bottles
- \* Coverage; Approx. 1lm per ml

### **SURFACE PREPARATION**

All sub-floor surfaces shall be dry, smooth, sound and clean, free of wax, grease, oil, old adhesive, paint, curing compounds, laitance, bond breakers and all other contaminants that inhibit adequate adhesion to the sub-floor. The sub-floor must also be free from hydrostatic pressure or capillary action. Glossy surfaces should be sanded to provide an adhesion key. The adhesive should not be used in excessive cold or hot conditions i.e. below 8°C or above 28°C. All subfloors should in accordance with current Australian standard installation practices.

### **APPLICATION**

Apply a thin squiggle bead from the squeeze bottle, ensure the bead is the width of the gripper. Please note, do not over apply this product as it will expand and take longer to dry. For faster setting, once the adhesive is applied, a mist of water with a spray gun is recommended. Once the adhesive is applied to the sub-floor place the carpet gripper into the adhesive. The stretch in method of carpet installation can commence approx. 1 hour after carpet gripper placement.

### **CLEAN UP**

Whilst wet, wipe with a dampened metholated spirits rag. Dry adhesive may only be mechanically removed.

### **CAUTION**

Do not allow adhesive to freeze, unaffected by freezing when dry. This adhesive has a 6 month shelf life.

**SAFETY DATA**

Wear protective clothing, gloves are essential, as the adhesive bonds well to skin. For further information refer to the material safety data sheet.

**VENTILATION**

Always make sure that there is adequate ventilation when using this adhesive.

**CONDITIONS OF SALE:** contain a limited warranty against manufacturing defects.

**NOTICE TO THE PURCHASER**

All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Users assume all risk and liability resulting from the use of this product and must confirm the suitability thereof by their own tests.

**CONTACT POINT:** Technical Manager  
**TELEPHONE:** (02) 9316 4655